



HPS 10

高压消音器

High Pressure Silencer



产品特点 Features

- **减少 1/10 的堵塞 1/10 Clogging reduction**
双层吸音材料,过滤效果不同,可减少阻塞。
Double-layer sound absorbing material with different filtration reduces clogging.
- **泄压装置 Standard integrated relief valve**
当消音器内部压力超过 1.8MPa 时,泄压阀将启动。
The relief valve will activate when the silencer's internal pressure exceeds 1.8 MPa.
- **噪音降低 35 dB(A) 35 dB(A) noise reduction**
- **维护性提升 Improved maintenance**
仅需拆卸螺栓,即可更换吸音材质,无需拆卸整个消音器。 By removing a bolt, the sound absorbing material can be replaced without removing the silencer.

产品规格 Specification

型号 Model	HPS 10
介质 Fluid	压缩空气 Compressed Air
工作压力 Operating pressure	0~40 bar
口径 Port Size	R 1"
环境/介质温度 Ambient/Media Temperature	0 +80°C
材质 Materials	螺丝、垫圈 Screw, washer : 镀锌钢 Steel zinc plated 滤芯、支架 Element, supports : 铝 Aluminium 滤网 Mesh : 镀锌铁 Iron zinc plated 壳体 Shell : 镀镍钢 : Steel nickel plate 多孔滤芯 Porous element : PP

外观尺寸 Overall Dimension

