



KLFMA Series

Digital Mass Flow Sensor




Ordering Code

KLFMA — — — — —

①	②	③	④	⑤	⑥
Series	Type	Flow Rate Range	Port Size	Mounting Bracket	Output Method
KLFMA	01 : Standard	25 : 0.2~25	F1 : G1/8”	－ : No Bracket R : Mounting Bracket	D : NPN output + Analog output (4~20mA)
		100 : 1~100	F2 : G1/4”		
		200 : 2~200			
	02 : High Flow	500 : 5~500	F4 : G1/2”		
		1000 : 10~1000			
		2000 : 20~2000	F6 : G3/4		


Cable Specification



Conductor	Nominal area	AWG26
	O.D.	About 0.5mm
Insulator	O.D.	About 1mm
	Color	Brown, White, Black, Blue
Casing	Material	Oil-resistant PVC
Finished O.D.		φ3.5

Internal Circuitry and Wiring

NPN + Analog Output



- Maximum applied voltage: 28V,
Maximum load current: 80mA,
Internal voltage drop: less than 1V
- D-analog output: 4~20mA
Load impedance: 50~600Ω



Digital Mass Flow Sensor

KLFMA Series

Specification

Series KLFMA								
Type			KLFMA 0125	KLFMA 01100	KLFMA 01200	KLFMA 02500	KLFMA 021000	KLFMA 022000
Fluid	Medium		Dry air, N ₂ , CO ₂ , Ar			Dry air, N ₂		
Flow	Flow Range (L/min)	Air,N2	0.2~25	1~100	2~200	5~500	10~1000	20~2000
		CO ₂	0.2~12.5	1~50	2~100	—	—	—
	Setting Flow Range	Instantaneous Flow	0.1 L/min		1 L/min		1 L/min	
		Cumulative Flow	1 L			10 L		
		Accumulated Pulse Output (L/pulse)		0.1	1	1	10	10
Pressure	Pressure Range		-0.1~0.75 MPa			0~0.8 MPa		
	Max. Pressure		1.0 MPa					
Electrical	Supply Power		DC12~24V±10%					
	Current Consumption		35mA 以下			55mA 以下		
Accuracy	Display Accuracy		±3% F.S. ±1 digit					
	Analog Output Accuracy		±3% F.S.					
	Repeat Accuracy		±1% F.S. ±1 digit (±2% F.S. ±1 digit when digital filter 0.05s is selected)					
	Temperature		±5% F.S. ±1 digit (0~50C: 25°C reference)					
Switch Output	Output Form		NPN open collector					
	Output Mode		Hysteresis mode/upper and lower limit comparison mode/accumulated pulse output mode Error output mode/switch output OFF mode					
	On/Off		NPN/PNP open collector					
	Max. Load Current		100mA					
	Max. Supply		DC30V					
	Internal Voltage Drop		NPN: 1V or less (load current 80mA)					
	Response Time		50ms or less					
	Short Circuit Protection		Yes					
Analog Output	Output Form		Current output: 4~20mA					
	Impedance	Voltage Output	Output impedance: about 1kΩ					
		Current Output	Maximum load impedance: 600Ω when power supply voltage is 24V, 300Ω when power supply voltage is 12V					
		Response Time		50ms±40%				



Digital Mass Flow Sensor


KLFMA Series

Specification

Series KLFMA							
Type		KLFMA 0125	KLFMA 01100	KLFMA 01200	KLFMA 02500	KLFMA 021000	KLFMA 022000
Display	Display Unit		STD, NOR				
	Display Mode		Instantaneous flow display / Accumulated flow display				
	Unit	Instantaneous Flow	L/min 、cfm				
		Cumulative Flow	L 、ft ³				
	Displayable Range	Cumulative Flow	-1.3~26.3	-5~105	-10~210	-25~525	-50~1050
		Forced Zero Range	0~±10%F.S. (For the maximum rated flow, select every 1%F.S.)				
		Accumulated Flow	0~999999999				
	Display		Display mode: LCD, Display color: red. green, Display digits: 4 digits 7 segments				
	Action Indicator Light		Out1/2 lights up when switch is ON: orange				
Environ-mental Resist-ance	Protection level		IP 40				
	Voltage Resistance		AC1000V (1 minute between lead and plastic housing)				
	Insulation Resistance		50 MΩ or more (DC500V, between lead and plastic housing)				
	Temperature Range		Action: 0~50°C, Storage: -10~60°C (no condensation, no freezing)				
	Humidity Range		Action, storage: 35-85%RH (no condensation, no freezing)				

Structural Material

No.	Name	Material
1	Casing	PBT+30%GF
2	Panel	PMMA
3	Panel bracket	PC black
4	Button	Silicone rubber
5	Connector	SUS304
6	Body	PPS+30%GF
7	Sealing ring	FKM
8	Filter	SUS304
9	Bracket	SUS304






Digital Mass Flow Sensor


KLFMA Series

Dimensions



Series	L	Port Size
KLFMA0125	66	G1/8
KLFMA01100	74	G1/4
KLFMA01200	74	G1/4

KLFMA02500 、KLFMA021000





Digital Mass Flow Sensor

KLFMA Series

Dimensions

KLFMA022000

